




Projectors... and more!

EIP-HDT30

Full HD 1080p DLP® Theater Projector

KEY FEATURES: Model EIP-HDT30

- Full HD 1080p resolution. 8,000 Lumens bright. 7,500:1 contrast ratio.
- Single Chip DLP® imaging technology delivers a "seamless" image.
- Upscales 720p. Supports other widescreen and standard aspect ratios.
- Included 6-segment dual color wheel set can be installed for rich color.
- 2 fixed inputs include a full suite of standard professional connections.
- 2 module bays permit customization. Built-in LAN Control Port.
- Optional modules include Dual (HD/SD) SDI and HD Wireless Receiver.
- Power Zoom and Focus. Optional Wideangle and Telephoto lenses.
- Both horizontal & vertical power lens shift. Built-in Mechanical shutter.
- Centered lens and one-way airflow simplify installation. Quick lens installation.
- Dual Lamp System provides redundancy and permits 4 brightness levels.
- Illuminated control panel & wireless/wired remote. RS-232 & Network control.
- Power Management, Keylock Security, and Custom Warmup Screen options.
- 3 Year Projector Warranty!



EIP-HDT30 (shown with optional lens)

Included Accessories: Quick Setup Guide, Owner's Manual on CD ROM. 6.0 ft. (1.8 M) AC Power Cord . Lens Cover. VGA-type Computer Input Cable (Dsub 15). Wireless/wired Remote & 2 x AA batteries. Wired Remote Cable. Real Color Manager Pro Software on CD-ROM. Lens Aperture Cover. Cable Cover x 1. Cable Cover Support x 1. Cable Cover Ties x 3. Rich Color 6-Segment Color Wheels x 2. Network Software on CD-ROM.

Optional Accessories: Wideangle, Standard and Telephoto Lenses. Replacement Lamps. Replacement Filter Cartridge. ATA-Style Shipping Case with Wheels and Telescoping Handle. Dual SDI Module (only HD-SDI can be used). DVI (only) Module. DVI-D & Dsub15 Module. 5BNC Module. 5BNC & S-Video Module. Dsub15 Module. Network Module. Ceiling Mount. Ceiling Post and Plate. HD Data Wireless Receiver Module. HD Wireless Transmitter.

Outstanding Features:

- 1.1080p at 8000 Lumens, 7500:1 Contrast, with DLP® imaging.
2. User-changeable color wheels to optimize brightness or color.
3. Lamp Interval Timer permits alternate 1-lamp-ON in 24/7 use.
4. Low Maintenance: up-to 35,000 hour cartridge air filter.
5. Extended Use: Peltier device cooled DMD®, sealed optical engine.
6. Picture-in-Picture. Picture-by-Picture. Edge Blending.
7. Power zoom, focus, lens shift. Range of lenses and modules.

SPECIFICATIONS: Model EIP-HDT30

Screen Brightness	up to 8,000 ANSI Lumens (**w/lens AH-43005S)	Video: Image Sizing	Video Scaling Technology
	("Dynamic" image mode & DynamicBlack™ Off)	Video: Resolutions Supported	
Illumination Uniformity	90%	SDTV (Composite, S-Video, Component)	480i/p, 575i/p
Size of Color Palette	10 bit / 1.07 Billion Colors	HDTV	720p, 1080i/p, 1080 psf 30/25/24
Contrast Ratio	over 7,500:1 (w/DynamicBlack™ high)	Signal Inputs: fixed	
Horizontal Resolution	550 TV Lines (HDTV)	1 a. Computer: Analog RGB	Dsub 15 x 1
Projection Lamp	330 Watt VIDITM UHP x 2	b. Computer: Digital RGB	DVI-D x 1
Estimated Lamp Life	up to 3000 Hours of Use	or Video: Digital Video w/HDCP	
Imaging System	0.95" DarkChip™ 1-chip DLP® x 1	c. Video: Digital Video w/HDCP	HDMI x 1
Native Resolution	1920x1080 (16:9 aspect ratio)	2 a. Computer: Analog RGBHV	BNC x 5
Color System	High Brightness 4-segment color wheels x 2 (installed)	or Video: Composite/Component: Video / Y-Pb/Cb-Pr	
Lens Type	Not Included (choose from a selection of optional lenses)	b. Video: S-Video:	S-Video x 1
Image Diagonal	50~600 in. (127~1524 cm)	Signal Inputs: Modules	
Image Width	3.64~43.6 ft. (1.11~13.20 m.)	3. Empty module bay (unpopulated)	
Throw Distance	See specifications of selected lenses	4. Empty module bay (unpopulated)	
Front Elevation / Maximum Pitch	up to 5° up / 360°	Signal Outputs:	
Vertical Anti Keystone	Power Lens Shift (Top:Bottom) 21:-1~1:21	Data/Video Monitor: Analog RGB / Composite/Component Dsub 15 x 1	
Horizontal Anti Keystone	Power Lens Shift (L:R~R:L) 3:1~1:3	Operating Noise	as low as 35 dBA
Vertical Keystone Correction	Digital: up to 30° up or down	Cabinet Size (HxWxD)	9.6 x 15.7 x 20.6 in. (242.5 x 400 x 524.2 mm.)
Horizontal Keystone Correction	Digital: up to 30° left or right	Weight	43.2 lb. (19.6 kg)
Scanning Frequency	Auto: H Sync. 15-120 kHz; V Sync. 48-120 Hz	Packaged Size	17.3 x 20.8 x 25.6 in. (439 x 528 x 651mm.)
Dot Clock	up to 230 MHz	Packaged Weight	54.2 lb (24.6 kg)
Image Orientation	Normal, Reversed, Inverted	Power Requirements	100-240V AC, 50/60Hz
Local Control / Power Management	Full Function / Auto Shut-Off	Power Consumption	up to 963W Standard Mode
Remote Projector Control	Wireless/wired x 1	Heat	up to 3286 BTU/hr.
Projector Service Port	USB-B x 1	Power Cord	Type 3, Detachable
Wired Remote Port	MiniStereo x 1	Electrical Safety Compliance	UL / cUL
RS-232 (Serial) Port / In & Out	Dsub 9-pin x 2	Electromagnetic Compatibility	FCC Part 15 Class A
Wired LAN Control Port	RJ45 x 1	Security	Kensington® Security Slot, Handles (use a Security Bar)
Computer: Compatibility	WUXGA (Analog only)	Operating Temperature	41~104°F (5~40°C)
	UXGA ~ WXGA, SXGA+ ~ VGA & MAC (analog & digital)	User Maintenance	Replace Air Filter, Replace Lamps
Computer: Formats	1920 x 1200 through 640 x 480	Warranty (to original end use customer)	
Computer: Image Sizing	Normal, or Smart Compressed or Expanded	Projector :	3 Years
Video: Color Systems	NTSC/PAL/SECAM/NTSC 4.43 / PAL-M&N	Lamp: ..	6 months ownership / 500 hours use (whichever occurs first)
Video: Aspect Ratios Supported	4:3 & 16:9		

Lamp contains Mercury. Do not put in trash. Dispose of as Hazardous Waste, according to Local, State or Federal Laws.

Specifications subject to change without notice. ©2010 Eiki International, Inc. Issued September 1, 2010.

Eiki International, Inc., 30251 Esperanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada: 310 First St., Unit 2, P.O. Box 156, Midland, ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, E-mail: canada@eiki.com

Visit our World Wide Web site: <http://www.eiki.com>